

STONIMAGE

How to be A Global Leader in Services?

Many of us are facing after-sales trouble no matter private or governmental control company, time is invaluable and most worrying for us. Once the machine shut down, the production shut down either, and we start to lose money quickly and come to an operation crisis So what we do here?

- Fast Action in Services
- Unconditional Parts Supply ٠
- Strong Professionalism ٠
- Spotless Satisfaction

This is how STONIMAGE started to make business. What we do is giving the fastest services after supplying high-quality level products.

XINXIANG STONIMAGE TECHNOLOGY CO. LTD 新乡市石像科技有限公司 Email: inquire@stonimage.com

Tel: +86 373 5853611 +86 173 3736 9213 www.stonimagelift.com Add: 1522#, Gongyuanguoji, Hongqi district, Xinxiang city, Henan, China

STONIMAGE

was founded at end of 2014, is a global brand and manufacturer of lifting equipment and material handling equipment, we owns the most professional engineering team, R & D center and manufacturing base with rich experience in lifting industry. We are working with full passion in continuous innovation and improving services level.

Currently, STONIMAGE is focusing on Innovation, Manufacturing and Supplying of various lifting equipment, transportation machinery and construction machinery, mainly as below:

- Ladder Lift, Solar Panel Lift, Glass and window lift, Glass trolley •
- Cargo truck elevator, Fish elevator, Mountain cargo Lift
- Electric scaffold, Wall building platform ٠
- Electric forklift, Brick stacker, Installation Forklift for Pipe/Panel
- Scissor lift, Retracble stairs, Belt conveyor
- Electric Food Lift •





- Aerial Ladder Lift
- ✓ For Solar panel
- ✓ For Glass/window/door
- ✓ For Construction material




- Cargo Truck Loader •
- Fish Truck Loader



- ✓ Max. Lifting Capacity: 30kg
 ✓ Lifting height: 2.5~8m
 ✓ For lifting food, drinks









Technical Data

| Platform Height (m) | Max. Lifting Capacity (kg) | Platform size (cm) | Dead weight (kg) | Tray Material |
|------------------------|-------------------------------|--------------------|------------------|---------------|
| 2.5 | 30 | 40*60*30 | 64 | 304 stainless |
| 3 | 30 | 40*60*30 | 67 | 304 stainless |
| 3.5 | 30 | 40*60*30 | 70 | 304 stainless |
| 4 | 30 | 40*60*30 | 73 | 304 stainless |
| 4.5 | 30 | 40*60*30 | 76 | 304 stainless |
| 5 | 30 | 40*60*30 | 79 | 304 stainless |
| 5.5 | 30 | 40*60*30 | 82 | 304 stainless |
| 6 | 30 | 40*60*30 | 87 | 304 stainless |
| 7 | 30 | 40*60*30 | 92 | 304 stainless |
| 8 | 30 | 40*60*30 | 97 | 304 stainless |

Technical Notes:

- Motor power: 250W
 Standard voltage: 220V
 Speed: Can be adjusted
 Control: Remote control

- 5) Track width: 37mm
- 6) Packing: Wooden case (especially for export)











